

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

VELTEK ASSOCIATES, INC. Date of issue: 11 January 2016 Revision date: N/A Supersedes: N/A Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : WIPEDOWN 1-2-3 (3) ALCOH-Wipe[®]
SDS code : SDS VEL-121-AW (ABN Process2Wipe)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Wipe for removal of contamination on clean room surfaces

1.3. Details of the supplier of the safety data sheet

Veltek Associates, Inc. 15 Lee Blvd Malvern, PA 19355-1234 USA T +1 610-644-8335 - F +1 610-644-8336 vai@sterile.com

1.4. Emergency telephone number

Emergency number : CARECHEM 24 call: 1-866-928-0789

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 2 H225 Eye Irrit. 2A H319 STOT SE 3 H336

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)





GHS02 GHS07

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapor H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

Precautionary statements (GHS-US) : P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking

P233 - Keep container tightly closed P261 - Avoid breathing vapors

P264 - Wash face, hands thoroughly after handling P271 - Use only outdoors or in a well-ventilated area

P280 - Wear eye protection, protective clothing, protective gloves

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P337+P313 - If eye irritation persists: Get medical advice/attention P403+P233 - Store in a well-ventilated place. Keep container tightly closed P501 - Dispose of contents/container to an authorized waste collection point

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

01/11/2016 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Isopropanol	(CAS No) 67-63-0	68 - 72	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice

(show the label where possible).

First-aid measures after inhalation : Not an expected route of exposure. First-aid measures after skin contact : Rinse skin with water/shower.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persist.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. If symptoms persist call a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause drowsiness or dizziness. Symptoms/injuries after eye contact : Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable.

Reactivity : Stable under normal conditions.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed

containers. Do not allow run-off from fire fighting to enter drains or water courses.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area. Avoid contact with skin and eyes.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if large amounts of the product enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Place in a suitable container for disposal in accordance with the waste regulations (see Section

13).

01/11/2016 EN (English US) 2/7

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.4. Reference to other sections

SECTION 8: Exposure controls/personal protection. SECTION 13: Disposal considerations.

SECTION 7: Handling and storage

Precautions for safe handling 7.1.

Precautions for safe handling

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of

Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep only in the original container in a cool, well ventilated place away from : Heat sources.

Keep container tightly closed.

7.3. Specific end use(s)

Wipe for removal of contamination on clean room surfaces.

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

Isopropanol (67-63-0)			
USA ACGIH	ACGIH TWA (ppm)	200 ppm	
USA ACGIH	ACGIH STEL (ppm)	400 ppm	
USA ACGIH	Remark (ACGIH)	Eye & URT irr; CNS impair	
USA OSHA	OSHA PEL (TWA) (mg/m³)	980 mg/m³	
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm	

8.2. **Exposure controls**

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection Wear protective gloves.

Eye protection Chemical goggles or safety glasses. Wear suitable protective clothing. Skin and body protection

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state : Liquid

Appearance Fabric moistened with liquid. Color White fabric, clear liquid.

Odor : mild. alcohol. : No data available Odor threshold

рΗ 5.5 - 7.5

Relative evaporation rate (butyl acetate=1) : No data available Melting point : Not applicable Freezing point : Not applicable Boiling point : 180.5 °F (82.5 °C) Flash point 64.9 °F (18.3 °C) Auto-ignition temperature : 750.2 °F (399 °C) Decomposition temperature : No data available Flammability (solid, gas) : No data available : 4.41 Pa

Vapor pressure Relative vapor density at 20 °C 1.6 (air = 1)

Relative density : 0.84

Solubility : No data available Log Pow : No data available Log Kow : No data available

01/11/2016 EN (English US) 3/7

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

: No data available Viscosity, kinematic Viscosity, dynamic : No data available Explosive properties : Not explosive. Oxidizing properties Not oxidizing.

: 2.5 - 12 vol % Isopropyl alcohol **Explosive limits**

Other information 9.2.

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. **Chemical stability**

Stable under normal conditions.

Possibility of hazardous reactions 10.3.

Will not occur.

10.4. **Conditions to avoid**

Keep away from heat. Ignition sources. Incompatible materials.

Incompatible materials

Strong oxidizing agents. Strong acids. alkali metals. Halogens. Bases. Metallic salts. Peroxides.

Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity : Not classified

Isopropanol (67-63-0)		
LD50 oral rat	4396 mg/kg	
LD50 dermal rat	12800 mg/kg	
LC50 inhalation rat (mg/l)	72.6 mg/l/4h	

Skin corrosion/irritation : Not classified

pH: 5.5 - 7.5

Serious eye damage/irritation Causes serious eye irritation.

pH: 5.5 - 7.5

Respiratory or skin sensitization Not classified Germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

: Not classified Carcinogenicity

IS	0	pr	op	an	OI ((b/	-63	-U)	

3 - Not classifiable IARC group

Reproductive toxicity : Not classified

Based on available data, the classification criteria are not met

Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.

Specific target organ toxicity (repeated : Not classified

exposure)

Based on available data, the classification criteria are not met

Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/injuries after inhalation : May cause drowsiness or dizziness.

Symptoms/injuries after eye contact : Causes serious eye irritation.

01/11/2016 EN (English US) 4/7

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. **Toxicity**

Ecology - water : Not classified.

Isopropanol (67-63-0)		
LC50 fish 11130 mg/l 96 h - Pimephales promelas		
LC50 other aquatic organisms 1400 mg/l 48 h - Crustaceans		
EC50 Daphnia	13299 mg/l 48 h - Daphnia magna	

12.2. Persistence and degradability

Isopropanol (67-63-0)	
Persistence and degradability	Expected to be readily biodegradable.

12.3. **Bioaccumulative potential**

Isopropanol (67-63-0)	
Bioconcentration factor (BCF REACH)	3

12.4. **Mobility in soil**

WIPEDOWN 1-2-3 (3) ALCOH-Wipe®	
Ecology - soil	No information available.

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN3175 Solids containing flammable liquid, n.o.s. Isopropyl alcohol, 4.1, II

UN-No.(DOT) : 3175 DOT NA no. : UN3175

Proper Shipping Name (DOT) : Solids containing flammable liquid, n.o.s.

Isopropyl alcohol

Transport hazard class(es) (DOT) : 4.1 - Class 4.1 - Flammable Solid 49 CFR 173.124

Hazard labels (DOT) : 4.1 - Flammable solid



DOT Symbols : G - Identifies PSN requiring a technical name

Packing group (DOT) : II - Medium Danger

01/11/2016 EN (English US) 5/7

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)

: 47 - Mixtures of solids that are not subject to this subchapter and flammable liquids may be transported under this entry without first applying the classification criteria of Division 4.1, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Except when the liquids are fully absorbed in solid material contained in sealed bags, each packaging must correspond to a design type that has passed a leakproofness test at the Packing Group II level. Small inner packaging consisting of sealed packets containing less than 10 mL of a Class 3 liquid in Packing Group II or III absorbed into a solid material are not subject to this subchapter provided there is no free liquid in the packet. IB6 - Authorized IBCs: Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N); Rigid plastics (11H1, 11H2, 21H1, 21H2, 31H1 and 31H2); Composite (11HZ1, 11HZ2, 21HZ1, 21HZ2, 31HZ1 and 31HZ2). Additional Requirement: Composite IBCs 11HZ2 and 21HZ2 may not be used when the hazardous materials being transported may become liquid during transport. IP2 - When IBCs other than metal or rigid plastics IBCs are used, they must be offered for transportation in a closed freight container or a closed transport vehicle.

T3 - 2.65 178.274(d)(2) Normal...... 178.275(d)(2)

TP33 - The portable tank instruction assigned for this substance applies for granular and powdered solids and for solids which are filled and discharged at temperatures above their melting point which are cooled and transported as a solid mass. Solid substances transported or offered for transport above their melting point are authorized for transportation in portable tanks conforming to the provisions of portable tank instruction T4 for solid substances of packing group III or T7 for solid substances of packing group II, unless a tank with more stringent requirements for minimum shell thickness, maximum allowable working pressure, pressure-relief devices or bottom outlets are assigned in which case the more stringent tank instruction and special provisions shall apply. Filling limits must be in accordance with portable tank special provision TP3. Solids meeting the definition of an elevated temperature material must be transported in accordance with the applicable requirements of this subchapter.

DOT Packaging Exceptions (49 CFR 173.xxx) 151 DOT Packaging Non Bulk (49 CFR 173.xxx) : 212 DOT Packaging Bulk (49 CFR 173.xxx) : 240 DOT Quantity Limitations Passenger aircraft/rail : 15 kg

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 50 kg

CFR 175.75)

DOT Vessel Stowage Location

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

Additional information

Other information : Not classified.

Special transport precautions : No special precautions required.

Transport by sea

UN-No. (IMDG) : 3175

Proper Shipping Name (IMDG) : SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S.

: 4.1 - Flammable solids, self-reactive substance and solid desensitized explosives Class (IMDG)

Packing group (IMDG) : II - substances presenting medium danger

Air transport

UN-No. (IATA) : 3175

Proper Shipping Name (IATA) : SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S.

Class (IATA) : 4.1 - Flammable solids Packing group (IATA) : II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

WIPEDOWN 1-2-3 (3) ALCOH-Wipe®	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

Isopropanol (67-63-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313

01/11/2016 EN (English US) 6/7

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

WIPEDOWN 1-2-3 (3) ALCOH-Wipe®	
WHMIS Classification	Class B Division 2 - Flammable Liquid
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects

National regulations 15.2.2.

No additional information available

15.3. US State regulations

Isopropanol (67-63-0)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

: US OSHA HazCom (GHS) 25 May 2012. Data sources

Other information This product has isopropyl rubbing alcohol impregnated on a wipe applicator. This SDS

represents the chemical.

Full text of H-phrases: see section 16:

Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

NFPA health hazard : 2 - Intense or continued exposure could cause temporary

incapacitation or possible residual injury unless prompt


medical attention is given.

NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all

ambient conditions.

0 - Normally stable, even under fire exposure conditions, NFPA reactivity

and are not reactive with water.



HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability 3 Serious Hazard Physical : 0 Minimal Hazard

NCEC SDS US GHS (Hazcom 2012)

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Veltek Associates, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Veltek Associates, Inc. accepts no liability for loss or damage resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

01/11/2016 EN (English US) 7/7